




### Model Number

NCN15-30GM40-Z1

### Features

- Comfort series
- 15 mm not embeddable
- 2-wire DC

### Connection




### Accessories

#### BF 30

Mounting flange, 30 mm

### Dimensions



### Technical Data

#### General specifications

Switching element function	DC	NC
Rated operating distance	$s_n$	15 mm
Installation		not embeddable
Output polarity		DC
Assured operating distance	$s_a$	0 ... 12.2 mm
Reduction factor $r_{A1}$		0.38
Reduction factor $r_{Cu}$		0.35
Reduction factor $r_{303}$		0.68

#### Nominal ratings

Operating voltage	$U_B$	5 ... 60 V
Switching frequency	$f$	0 ... 100 Hz
Hysteresis	$H$	1 ... 10 typ. 5 %
Reverse polarity protected		tolerant
Short-circuit protection		pulsing
Voltage drop	$U_d$	$\leq 5$ V
Operating current	$I_L$	2 ... 100 mA
Lowest operating current	$I_m$	2 mA
Off-state current	$I_r$	0 ... 0.5 mA typ.
Indication of the switching state		all direction LED, yellow

#### Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

#### Mechanical specifications

Connection type	cable PUR, 2 m
Core cross-section	0.34 mm <sup>2</sup>
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	PBT
Protection degree	IP67

#### Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

#### Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Certified by China Compulsory Certification (CCC)